



Model Number: **7-7-900 (1200m3/h)**

Description

Overall Efficiency: 33.4%
Measurement Type: A
Efficiency type: Static
FMEG: N=44.2
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 240W
Input Current: 1,12A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:



Model Number: **7-7-1400 (1500m3/h)**

Description

Overall Efficiency: 34.83%
Measurement Type: A
Efficiency type: Static
FMEG: N=44.2
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 245W
Input Current: 1,15A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:



Model Number: **12-12-1100 (7000m3)**

Description

Overall Efficiency: 37.45%
Measurement Type: A
Efficiency type: Static
FMEG: N=44.2
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 1450W
Input Current: 1.60A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:



Model Number: **9-9-9001/3 (2500m3)**

Description

Overall Efficiency: 45.00%
Measurement Type: A
Efficiency type: Static
FMEG: N=50.2
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 400W
Input Current: 1.92A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:





Model Number: **9-9-1400 (3250m3)**

Description

Overall Efficiency: 36.8%
Measurement Type: A
Efficiency type: Static
FMEG: N=44.5
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 480W
Input Current: 2.4A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:



Model Number: **10-10-1400 (4250m3)**

Description

Overall Efficiency: 38.0%
Measurement Type: A
Efficiency type: Static
FMEG: N=44.2
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 1100W
Input Current: 5.25A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:



Model Number: **12-9-900 (5000m3)**

Description

Overall Efficiency: 37.1%
Measurement Type: A
Efficiency type: Static
FMEG: N=45
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 1450W
Input Current: 6A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:



Model Number: **12-12-900 (6000m3)**

Description

Overall Efficiency: 37.6%
Measurement Type: A
Efficiency type: Static
FMEG: N=44.2
Measurement: without VSD
VSD: install with VSD
Electrical Supply: 230V 50Hz
Insulation Class: F
Input Power: 1400W
Input Current: 6.5A
IP Rating: IP20

AIRFAN® P.O. Box 25, NL- 5170 AA KAATSHEUVEL - The Netherlands

Production date:

